POS 187 3 313 B

Optical Liquid Level Sensors for Standard Temperatures

Technical parameters

Nominal Voltage Un
24 VDC

Supply Voltage Uc
12 – 30 VDC

Supply Current Ic
< 25 mA

Output Current Iz
? 200 mA

Switching Frequency
35 Hz

Short-Circuit Protection
Yes

Polarity Reversal Protection
Yes

Maximum Operating Pressure
2 MPa

Output Type
PNP no

Housing Material
Stainless Steel AISI 303

Operating Temperature – Process
-25°C…+100°C

Operating Temperature – Ambient
-25°C…+80°C

Output Indicator
LED

Output Type
Cable PVC 3 x 0,25 mm2

Cable Length
2 m

Protection Standard
IP 68

Sensing Tip Material
Borosilicate Glass

Use
Foamy liquids (e.g. beer, sodas), “does not see the foam”

Product image

Dimensions





Company Head Office
PLOSKON AT s.r.o.
Jesenná 1
080 01 Prešov
Slovak Republic

Telephone
+421 / (0)51 7732 836
+421 / (0)51 7731 003

E-mail
obchod@ploskon.sk

Website
www.ploskon.sk

Billing information
PLOSKON AT s.r.o.
I?O:36483354
DI?:2020009860

Generated on October 14, 2026