

PAS 063 313 S

Inductive Proximity Sensors

Product image



Technical parameters

Nominal Sensing Distance Sn
1,5 mm

Effective Sensing Distance Sr
1,2 - 1,8 mm

Housing Dimensions
ø 6,5

Mounting
Non-Flush

Hysteresis
(0,1 -0,15) x Sn

Nominal Voltage Un
24 VDC

Supply Voltage Uc
10 - 30 VDC

Supply Current Ic
< 10 mA

Output Current Iz
≤ 200 mA

Switching Frequency
50 Hz

Short-Circuit Protection
Yes

Polarity Reversal Protection
Yes

Output Type
PNP no

Housing Material
Nickel Plated Brass

Ambient Temperature Range T
-25°C...+70°C



Target Presence Indicator
LED

Output Type
Cable PVC 3 x 0,25 mm²

Cable Length
2 m

Protection Standard
IP 68

Dimensions



Company Head Office Telephone

PLOS KON AT s.r.o.
Jesenná 1
080 01 Prešov
Slovak Republic

+421 / (0)51 7732 836
+421 / (0)51 7731 003

E-mail

obchod@ploskon.sk

Website

www.ploskon.sk

Billing information

PLOS KON AT s.r.o.
IČO:36483354
DIČ:2020009860