PDI 128 314 35 S

Inductive Sensors with Double Switching Distance

Technical parameters

Nominal Sensing Distance Sn
8 mm

Effective Sensing Distance Sr
6 – 10 mm

Housing Dimensions
M12

Mounting
Non-Flush

Hysteresis
(0,1 -0,15) x Sn

Nominal Voltage Un
24 VDC

Supply Voltage Uc
10 – 30 VDC

Supply Current Ic
< 10 mA

Output Current Iz
? 200 mA

Switching Frequency
50 Hz

Short-Circuit Protection
Yes

Polarity Reversal Protection
Yes

Output Type
PNP nc

Housing Material
Nickel Plated Brass

Ambient Temperature Range T
-25°C…+70°C

Target Presence Indicator
LED

Output Type
Cable PVC 3 x 0,25 mm2

Cable Length
2 m

Protection Standard
IP 68

Product image



Dimensions





Company Head Office
PLOSKON AT s.r.o.
Jesenná 1
080 01 Prešov
Slovak Republic

Telephone
+421 / (0)51 7732 836
+421 / (0)51 7731 003

E-mail
obchod@ploskon.sk

Website
www.ploskon.sk

Billing information
PLOSKON AT s.r.o.
I?O:36483354
DI?:2020009860

Generated on November 23, 2026