


# PPI 129 111

Higher Pressure Resistant Inductive Proximity Switches



## Technical parameters

<b>Nominal Sensing Distance Sn</b> 1,2 mm	<b>Effective Sensing Distance Sr</b> 0,9 - 1,5 mm
<b>Housing Dimensions</b> M12	<b>Mounting</b> Flush
<b>Hysteresis</b> (0,1 -0,15) x Sn	<b>Nominal Voltage Un</b> 24 VDC
<b>Supply Voltage Uc</b> 10 - 30 VDC	<b>Supply Current Ic</b> < 10 mA
<b>Output Current Iz</b> ≤ 200 mA	<b>Switching Frequency</b> 1 kHz
<b>Short-Circuit Protection</b> Yes	<b>Polarity Reversal Protection</b> Yes
<b>Pressure Resistance</b> < 5 MPa	<b>Output Type</b> NPN no
<b>Housing Material</b> Stainless Steel AISI 303	<b>Ambient Temperature Range T</b> -25°C...+80°C
<b>Output Type</b> Cable PVC 3 x 0,25 mm <sup>2</sup>	<b>Cable Length</b> 2 m
<b>Protection Standard</b> IP 68	

## Product image



## Dimensions



## Company Head Office Telephone

PLOSKON AT s.r.o.  
Jesenná 1  
080 01 Prešov  
Slovak Republic

## E-mail

obchod@ploskon.sk

## Website

www.ploskon.sk

## Billing information

PLOSKON AT s.r.o.  
IČO:36483354  
DIČ:2020009860